

safetrack[®] sc patch pack

ROAD COLOUR

DESCRIPTION

Safetrack SC is a liquid applied, fast curing, UV stable, slip resistant road colour coating based on our advanced MMA technology.

The **PATCH PACK** contains all the necessary materials and equipment to successfully and easily apply the material.

USES

Designed to provide a highly visible, slip resistant demarcation coating the system is ideal for a wide variety of trafficked and pedestrian areas including:

- Utility reinstatement
- Bus lanes
- Cycle lanes
- Traffic calming
- Home zones
- Refreshing faded thermoplastics

FEATURES

- Permanent, first time reinstatement
- Quick, simple and economical to apply
- Cold applied – no hot trades
- Excellent adhesion to a variety of substrates
- Long term colour stability
- Longer service life – less maintenance
- Fast return to service
- Self contained application kit

TECHNICAL DATA

PROPERTY	VALUE
Application Temperature Range ⁽¹⁾	0 to 30°C
Typical Working Life	
20°C	12 minutes
0°C	25 minutes
Drive on Time	
20°C	40 minutes
0°C	60 minutes
Skid Resistance Value (TRL Pendulum)	Average > 55 ² Typically 55 - 60

SURFACE PREPARATION

All substrates must be clean, dry and structurally sound. Dry with a gas burner if required.

APPLICATION

Full, easy to follow pictorial Application Guidelines are supplied with every patch pack.

COVERAGE

Typically 2m² per patch pack

COLOURS

Safetrack SC Patch Packs are available in Chrome Green and Road Red.

PACKAGING & STORAGE

Safetrack SC Patch Packs are supplied in a single container, containing all components and equipment to successfully apply the material.

All components should be stored in cool, dry, protected conditions, out of direct sunlight and in accordance with the relevant site Health & Safety regulations. Storage temperature must not exceed 25°C. Do not store near naked flames or foodstuffs.

Stored in unopened containers, under these conditions, the components have a shelf life of twelve months.

HEALTH & SAFETY

The Material Safety Data Sheet must be read, understood and available on site before commencing work.

Once all the material is cured the empty packaging can be disposed of as Industrial waste in accordance with Local Authority Guidelines.

It is the Company's policy to take all reasonable steps to prevent injury to all property and personnel from foreseeable hazards. This extends to the public in so far as they come into contact with the Company or its products.

GENERAL INFORMATION

Safetrack SC Patch Pack is part of a wide range of specialist highways maintenance, waterproofing, surfacing and repair materials manufactured and supplied by Stirling Lloyd. If you require any further information on this or any other of our products, please contact us or visit our website www.stirlinglloyd.com or our dedicated micro site:

"The" Highway Maintenance Range from Stirling Lloyd
www.highwaymaintenanceproducts.com



® SAFETRACK is a registered trademarks of Stirling Lloyd Polychem Ltd
© 2009 Stirling Lloyd Polychem Ltd.

The information presented herein is accurate to the best of our knowledge. We pursue a progressive research and development policy and reserve the right to alter any of the details herein without notice. The information given must not be taken in any way to form a specification. All technical properties quoted are from laboratory prepared samples. We will not accept liability whatsoever arising out of the use of the information contained herein.

Union Bank, King Street, Knutsford, Cheshire, WA16 6EF, England
Tel: +44 (0) 1565 633111 Fax: +44 (0) 1565 633555
E-Mail: info@stirlinglloyd.com
www.highwaymaintenanceproducts.com
www.stirlinglloyd.com

¹ For temperatures outside this application range please contact us.

² Per BS7976:2002 on texture depths up to 1.5mm. Mean of three consistent swings averaged over four areas. (Maximum area variation expected +/- 6)