



safetrack® overbanding

High Performance Overbanding System

products in action

Safetrack Overbanding has been designed for the overbanding of cracks in asphalt and concrete substrates, as well as the cracks between reinstatement materials and the existing road. It is also ideally suited for the sealing and infilling of fretted joints and in asphalt pavements.

A cold applied, asphalt grey rapid curing system based on Stirling Lloyd's advanced methyl methacrylate (MMA) technology, Safetrack Overbanding is the only system available to offer a high skid resistance throughout it's working life.

Providing exceptional resistance to wear, withstanding the insistent abrasion caused by high volume traffic, which can lead to cracking and even pot holes forming in asphalt and concrete roads Safetrack Overbanding offers:

- rapid cure enabling return of the network to service within 1 hour
- widest temperature range of application, enabling year round application from a single product
- excellent resistance to wear
- long term skid resistance
- fast and easy application, with no special tools or training required, and easy to follow step-by-step instructions
- a non-reflective matt surface
- low health risk to users, with no hot trades
- dimensionally stable resistance to most common chemicals, fuels and oils
- extends the service life of asphalt, reducing maintenance

Safetrack Overbanding is:

- **Safe to Use**
- **Safe & Effective In-Service**
- **The cost effective, simple, long term solution to the problem of cracks in concrete and asphaltic road surfaces.**



Also available for the high speed reinstatement of the Highways Network, based on our MMA technology, offering fast return to service, 24/7 working, requiring minimal specialist equipment are the following cold applied systems:

- | | |
|--------------|--|
| Safetrack HW | - Type 1 HAPAS high friction surfacing |
| Safetrack SC | - Road Colour |
| Safetrack LM | - Road Markings |
| Metaset EPM | - Patching Material |



Before



After

Ref. PIA_Safe034(2).pdf
Available from stirlinglloyd.com



STIRLING LLOYD UK & WORLD WIDE

Stirling Lloyd Polychem Ltd.
Union Bank . King Street . Knutsford
Cheshire . WA16 6EF . UK

Tel: +44 (0) 1565 633111
Fax: +44 (0) 1565 633555
Email: info@stirlinglloyd.com

STIRLING LLOYD NORTH AMERICA

www.northamerica.stirlinglloyd.com

The information contained in this literature is accurate to the best of the publisher's knowledge and we reserve the right to alter any of the details contained herein without notice. It must not be taken in any way to form a specification and Stirling Lloyd accepts no liability whatsoever arising out of the use of the information contained herein. This documentation does not form part of the 'Conditions of Sale' of our products.

THE TECHNOLOGY OF PROTECTION

www.stirlinglloyd.com