

safetrack[®] hw patch pack

ANTI-SKID PATCH REPAIR

DESCRIPTION

Safetrack HW is a liquid applied anti-skid system designed for localised areas of anti-skid. It is suitable for the rapid, permanent reinstatement of damaged or compromised road surfaces or for the reinstatement of anti-skid after maintenance work.

Safetrack HW is a Type 1 certified BBA/HAPAS High Friction Surfacing System that also conforms to Clause 924 of the UK Specification for Highway Works (March 1998) for Resin Based High Skid Resistant Surface Treatments.

The **PATCH PACK** contains all the necessary materials and equipment to successfully and easily apply the material.

FEATURES

- Offers Permanent, first time reinstatement
- Quick, simple and economical to apply
- Cold applied – no hot trades
- Excellent adhesion to a variety of substrates
- Longer service life – less maintenance
- Fast return to service
- Self-contained application kit

TECHNICAL DATA

PROPERTY	VALUE
Application Temperature Range ¹	0°C to 30°C
Typical Working Life	
20°C	7 minutes
0°C	10 minutes
Typical Cure / Drive On Time	
20°C	30 minutes
0°C	55 minutes

SURFACE PREPARATION

All substrates must be clean, dry and structurally sound. Dry with a gas burner if required.

APPLICATION

Each patch pack contains an easy to follow step by step pictorial guide covering.

COVERAGE

Typically 2m² per patch pack.

Application onto Stone Mastic Asphalt (SMA), and other types of porous asphalt may lead to an increase in the required coverage rate.

AGGREGATES & COLOUR

1-3mm bauxite is included in the pack.

Standard colours are Buff or Grey.

PACKAGING & STORAGE

Safetrack HW Patch Pack is supplied in a single container with all the necessary materials and equipment to apply the product.

All components should be stored in cool, dry, protected conditions, out of direct sunlight and in accordance with the relevant site Health & Safety regulations. Storage temperature must not exceed 25°C. Do not store near naked flames or foodstuffs.

Stored in unopened containers, under these conditions, the components have a shelf life of 12 months.

LIMITATIONS

Do not apply Safetrack HW on to surface dressings or Bitmac surfaces.

HEALTH & SAFETY

The Material Safety Data Sheet must be read, understood and available on site before commencing work.

Once all the material is cured the empty packaging can be disposed of as Industrial waste in accordance with Local Authority Guidelines.

It is the Company's policy to take all reasonable steps to prevent injury to all property and personnel from foreseeable hazards. This extends to the public in so far as they come into contact with the Company or its products.

GENERAL INFORMATION

Safetrack HW Patch Pack is just one of a wide range of specialist highway maintenance, surfacing, waterproofing and repair materials manufactured and supplied by Stirling Lloyd. If you require any further information, please contact us or visit our main website, www.stirlinglloyd.com or our dedicated micro site:

**“The” Highway Maintenance Range
from Stirling Lloyd**

Visit: www.highwaymaintenanceproducts.com



® SAFETRACK is a registered trademark of Stirling Lloyd Polychem Ltd.
© 2008 Stirling Lloyd Polychem Ltd.

The information presented herein is accurate to the best of our knowledge. We pursue a progressive research and development policy and reserve the right to alter any of the details herein without notice. The information given must not be taken in any way to form a specification. All technical properties quoted are from laboratory prepared samples. We will not accept liability whatsoever arising out of the use of the information contained herein.

Union Bank, King Street, Knutsford, Cheshire, WA16 6EF, England
Tel: +44 (0) 1565 633111 Fax: +44 (0) 1565 633555
E-Mail: info@stirlinglloyd.com
www.highwaymaintenanceproducts.com
www.stirlinglloyd.com

¹ For temperatures outside this range, please contact us.