

safetrack[®] *lm patch pack*

COLD PLASTIC ROAD MARKINGS

DESCRIPTION

Safetrack LM is a range of genuine high-performance cold-plastic road marking systems that are based on our advanced MMA Technology.

The systems offer improved design life and durability and overcome the shortcomings found in today's traditional marking products with a product that provides the safety and guidance intended.

The **PATCH PACK** contains all the necessary materials and equipment to successfully and easily apply the material.

USES

There are currently two products in the Safetrack LM Patch Pack range, namely:

Durable: a hard wearing, economical road marking

Retromax: a solid road marking for highways

Special grades are available for use as:

- Red route road markings
- Deceleration bars

FEATURES

- UK Highways Agency Approved
- Permanent, first time reinstatement
- Quick, simple and economical to apply
- Cold applied – no hot trades
- Long service life – less maintenance
- Fast return to service
- Enhanced dry and wet night retroreflectivity
- Excellent skid resistance – retained in the long term
- Superb adhesion to a wide variety of substrates
- Self contained application kit

TECHNICAL DATA

Application Temperature Range ⁽¹⁾	0 to 30°C	
Typical Working Life	20°C	3 minutes
	0°C	5 minutes
Drive on Time	20°C	12 minutes
	0°C	35 minutes

SURFACE PREPARATION

Ensure the road surface to be marked is clean and dry before application.

Use a stiff brush to remove dust and loose material.

Dry using suitable means e.g. gas burner or oil free compressed air.

APPLICATION

Detailed, easy to follow pictorial Application Guidelines are supplied with every pack.

COVERAGE

Retromax – 2 linear metres per patch pack
(based on a 1mm deep, 100mm wide line)

Durable – 3.5 linear metres per patch pack
(based on a 2mm deep, 100mm wide line)

The required coverage rate will vary with surface texture and porosity.

COLOURS

Safetrack LM Patch Packs are available in the following colours:

Retromax - White

Durable - Yellow, Primrose & Red Route

PACKAGING & STORAGE

Safetrack LM Patch Packs are supplied in boxes containing 8 patch packs, which include all the materials and equipment to apply the system.

Safetrack 'Drop-on' Glass Beads are supplied with the Safetrack LM Retromax Patch Packs.

All components of the Safetrack LM Patch Pack system should be stored in cool, dry, protected conditions, out of direct sunlight and in accordance with the relevant site Health & Safety regulations. Storage temperature must not exceed 25°C. Do not store near naked flames or foodstuffs.

Stored in unopened containers, under these conditions, the components have a shelf life of twelve months.

HEALTH & SAFETY

The Material Safety Data Sheet must be read, understood and available on site before commencing work.

Once all the material is cured the empty packaging can be disposed of as Industrial waste in accordance with Local Authority Guidelines.

It is the Company's policy to take all reasonable steps to prevent injury to all property and personnel from foreseeable hazards. This extends to the public in so far as they come into contact with the Company or its products.

GENERAL INFORMATION

Safetrack HW Patch Pack is just one of a wide range of specialist highway maintenance, surfacing, waterproofing and repair materials manufactured and supplied by Stirling Lloyd. If you require any further information, please contact us or visit our main website, www.stirlinglloyd.com or our dedicated micro site:

**“The” Highway Maintenance Range
from Stirling Lloyd**

Visit: www.highwaymaintenanceproducts.com

¹ For application outside of these temperatures please contact our Customer Services Department.

safetrack[®] 1m patch pack

COLD PLASTIC ROAD MARKINGS



® SAFETRACK is a registered trademark of Stirling Lloyd Polychem Ltd.
© 2008 Stirling Lloyd Polychem Ltd.

The information presented herein is accurate to the best of our knowledge. We pursue a progressive research and development policy and reserve the right to alter any of the details herein without notice. The information given must not be taken in any way to form a specification. All technical properties quoted are from laboratory prepared samples. We will not accept liability whatsoever arising out of the use of the information contained herein.

Union Bank, King Street, Knutsford, Cheshire, WA16 6EF, England

Tel: +44 (0) 1565 633111 Fax: +44 (0) 1565 633555

E-Mail: info@stirlinglloyd.com

www.highwaymaintenanceproducts.com

www.stirlinglloyd.com